## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: IMMAX

Supplier's address: obchod, Teslova 1179/2, 70200 Ostrava, CZ

## Model identifier: 08930L

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	LED				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	Ne		
Colour-tuneable light source:	Ne	Envelope:	-		
High luminance light source:	Ne				
Anti-glare shield:	Ne	Dimmable:	Yes		
Product parameters					

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
•.	mption in on- 000 h), rounded est integer	9	Energy efficiency class	E		
indicating if it in a sphere (3)	us flux (φuse), refers to the flux 860º), in a wide in a narrow cone	450 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	30006000		
On-mode expressed in W	power (P <sub>on</sub> ),	6,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
for CLS, expre	ndby power (P <sub>net</sub> ) essed in W and e second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer	Height	360	Spectral power	See image		
dimensions	Width	182	distribution in the	in last page		
without	Depth	139		Strana 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity	0,313			
		coordinates (x and y)	0,337			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	20	Survival factor	1,00			
the lumen maintenance factor	1,00					
(a)		I. J.				

(a)<sub>'-'</sub> : not applicable;

(b)'-' : not applicable;

